

## Hylte Attract Plus



Hylte Attract is an improved newsprint grade. Made from 100% thermomechanical pulp.

- Outstanding runnability
- Fantastic in four colour printing

#### TYPICAL END USES

Inserts  
Advertisements  
Magazines  
Special Newspapers  
Free sheets

#### CERTIFICATES

Quality ISO 9001  
Environment ISO 14001  
Health & Safety ISO 45001  
Energy ISO 50001  
EU Eco label

#### REEL SPECIFICATIONS

Reel width: 2400 mm  
Reel diameter: 1250 mm  
Core: 76 mm  
Max trimmed width: 8400 mm

L\* 87.0  
a\* -0.3  
b\* 2.1

ISO 5631-1 (C/2°)

#### PRINTING METHODS

CSWO  
HSWO  
Flexo

### TECHNICAL SPECIFICATIONS - (target values)

Substance	ISO 536	g/m <sup>2</sup>	49	52	55	60	65	70
Brightness	ISO 2470-1 (C/2°)	%	72	72	72	72	72	72
CIE Whiteness	ISO 11476 (C/2°)	%	61	61	61	61	61	61
Bulk	ISO 534	cm <sup>3</sup> /g	1.6	1.6	1.6	1.6	1.6	1.6
Opacity	ISO 2471	%	91	92	93	94	95	96
Thickness	ISO 534	µm	79	84	90	95	103	110
Smoothness	PPS 1MPa, ISO 8971-4	µm	3.6	3.6	3.6	3.6	3.6	3.6
Roughness	Bendtsen ISO 8791-2	ml/min	100	100	100	100	100	100

#### STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.