

Hylte News



Hylte News is a standard newsprint grade. Made from 100% thermomechanical pulp.

- Outstanding runnability
- Fantastic in four colour printing
- Produced according to Ifra standard

TYPICAL END USES

Newspapers
Supplements
Free sheets

PRINTING METHODS

CSWO
(HSWO)

CERTIFICATES

Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
EU Eco label

REEL SPECIFICATIONS

Reel width: 2400 mm
Reel diameter: 1250 mm
Core: 76 mm
Max trimmed width: 8400 mm

L* 83.0
a* -0.7
b* 4.8

ISO 5631-1 (C/2°)

TECHNICAL SPECIFICATIONS - (target values)

Substance	ISO 536	g/m ²	38	40	42.5	45	48.8
Brightness	ISO 2470-1 (C/2°)	%	57	57	57	57	57
Opacity	ISO 2471	%	89	91	92	94	94
Thickness	ISO 534	µm	63	67	70	74	80
Smoothness	PPS 1MPa, ISO 8971-4	µm	3,9	3.9	3.9	3.9	3.9
Roughness	Bendtsen ISO 8791-2	ml/min	100	100	100	100	100

STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.