

Hylte Appetite Premium



Hylte Appetite is designed to be in contact with dry, moist and fatty food and foodstuff. Made from 100% thermomechanical pulp.

- Excellent paper for food packaging
- Fantastic in printing
- ISEGA certified product
- Available from 49 gsm up to 70 gsm

TYPICAL END USES

- Protective food packaging and wrapping solutions
- Interleaving for food preparation and production lines
- Liner and fluting for corrugated products.

CERTIFICATES

Quality ISO 9001
 Environment ISO 14001
 Health & Safety ISO 45001
 Energy ISO 50001
 EU Eco label
 ISEGA certified product

REEL SPECIFICATIONS

Reel width range: 310 - 2400 mm
 Max reel diameter: 1250 mm
 Max trimmed width: 8400 mm

TECHNICAL SPECIFICATIONS - (target values)

| Substance | ISO 536 | g/m ² | 49 | 52 | 55 | 60 | 65 | 70 |
|------------|----------------------|------------------|-----|-----|-----|-----|-----|-----|
| Brightness | ISO 2470-1 (C/2°) | % | 70 | 70 | 70 | 70 | 70 | 70 |
| Opacity | ISO 2471 | µm | 87 | 88 | 89 | 90 | 91 | 92 |
| Thickness | ISO 534 | ml/min | 88 | 93 | 98 | 107 | 116 | 126 |
| Smoothness | PPS 1MPa, ISO 8971-4 | µm | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 |

STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.