

Hylte Attract



Hylte Attract is an improved newsprint grade. Made from 100% thermomechanical pulp.

- Outstanding runnability
- Fantastic in four colour printing

TYPICAL END USES

Inserts
 Advertisements
 Magazines
 Special Newspapers
 Free sheets

PRINTING METHODS

CSWO
 HSWO
 Flexo

CERTIFICATES

Quality ISO 9001
 Environment ISO 14001
 Health & Safety ISO 45001
 Energy ISO 50001
 EU Eco label
 FSC® C221886
 PEFC/05-35-366

REEL SPECIFICATIONS

Reel width: 310-2400 mm
 Reel diameter: 1250 mm
 Core: 76 mm
 Max trimmed width: 8400 mm

L* 86.0
 a* -0.3
 b* 2.1

ISO 5631-1 (C/2°)

TECHNICAL SPECIFICATIONS - (target values)

Property	ISO Standard	Unit	Target 1	Target 2	Target 3
Substance	ISO 536	g/m ²	45	49	52
Brightness	ISO 2470-1 (C/2°)	%	68	68	68
CIE Whiteness	ISO 11476 (C/2°)	%	56	56	56
Opacity	ISO 2471	%	91	92	94
Thickness	ISO 534	µm	75	80	83
Smoothness	PPS 1MPa, ISO 8971-4	µm	3.9	3.9	3.9
Roughness	Bendtsen ISO 8791-2	ml/min	100	100	100

STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.