

Hylte Attract Plus



Hylte Attract is an improved newsprint grade. Made from 100% thermomechanical pulp.

- Outstanding runnability
- Fantastic in four colour printing

TYPICAL END USES

Inserts
Advertisements
Magazines
Special Newspapers
Free sheets

PRINTING METHODS

CSWO
HSWO
Flexo

CERTIFICATES

Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
EU Eco label
FSC® C221886
PEFC/05-35-366

REEL SPECIFICATIONS

Reel width: 310-2400 mm
Reel diameter: 1250 mm
Core: 76 mm
Max trimmed width: 8400 mm

L* 89.0
a* -0.3
b* 2.1

ISO 5631-1 (C/2°)

TECHNICAL SPECIFICATIONS - (target values)

Substance	ISO 536	g/m ²	49	52	55	60
Brightness	ISO 2470-1 (C/2°)	%	72	72	72	72
CIE Whiteness	ISO 11476 (C/2°)	%	61	61	61	61
Opacity	ISO 2471	%	91	92	93	94
Thickness	ISO 534	µm	79	84	87	94
Smoothness	PPS 1MPa, ISO 8971-4	µm	3.6	3.6	3.6	3.6
Roughness	Bendtsen ISO 8791-2	ml/min	100	100	100	100

STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.