

Hylte Appetite Prime



Hylte Appetite is designed to be in contact with dry, moist and fatty food and foodstuff. Made from 100% thermomechanical pulp.

- Excellent paper for food packaging
- Fantastic in printing
- ISEGA certified product
- Available from 38 gsm up to 45 gsm

TYPICAL END USES

- Protective food packaging and wrapping solutions
- Interleaving for food preparation and production lines
- Liner and fluting for corrugated products.

CERTIFICATES

Quality ISO 9001
 Environment ISO 14001
 Health & Safety ISO 45001
 Energy ISO 50001
 EU Eco label
 FSC® C221886
 PEFC/05-35-366
 ISEGA certified product

REEL SPECIFICATIONS

Reel width range: 310 - 2400 mm
 Max reel diameter: 1250 mm
 Max trimmed width: 8400 mm

TECHNICAL SPECIFICATIONS - (target values)

Substance	ISO 536	g/m ²	38**	40	42.5	45
Brightness	ISO 2470-1 (C/2°)	%	58	58	58	58
Opacity	ISO 2471	%	89	91	92	94
Thickness	ISO 534	µm	63	67	70	74
Smoothness	PPS 1MPa, ISO 8971-4	µm	3.9	3.9	3.9	3.9

** = Available depending on trim and ordered volumes

STORAGE AND HANDLING

- The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C - 23°C.
- If stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.